

Huestone All Stone Pre-Seal is a water-based sealer, which is designed to stop water absorption during the cleaning process. Once sealed, it will reduce salt transmission, mildew and efflorescence build up. Suitable on all porous earthen materials and can also be used internally or externally in domestic, commercial or light industrial applications. Huestone All Stone Pre-Seal is a durable fast curing and non-flammable sealer.

Benefits

- Stops water absorption during cleaning.
- Reduces salt transmissions, mildew and efflorescence build up.
- Durable fast curing and non-flammable.
- Suits all porous earthen material and can be used internally or externally.

Application

- ⇒ Ensure the surface is free from grease and dirt and that any prior coatings have been removed.
- ⇒ For heavily soiled floors it is recommended that a combination of Huestone Heavy Duty Degreaser (HDD) and Huestone Neutral Clean are used.
- ⇒ Once the floor is free from contamination and dry, the sealing process can start.
- ⇒ Always test product on a small area first. And allow a 24-hour cure time to determine the ease of application and desired results.
- ⇒ One coat of Huestone All Stone Pre-Seal should be applied with a low-pressure pump or a lambs wool applicator.

- ⇒ Allow 10 minutes for product to penetrate surface then wipe off excess with a clean white dry cloth.
- ⇒ Important - do not allow pre-seal to pool on surface.
- ⇒ The coat coverage rate will vary between 5 and 15sqm/ltr depending on the porosity of the material.
- ⇒ Allow drying time of around 60 minutes between coats depending on weather and humidity. The surface should be allowed 24 hours to fully cure.

Physical Properties

Colourless, clear to hazy
Odourless
PH 13
Specific gravity 1 solution.

Coverage

N/A

Packaging

Available in 1, 5, 20ltr containers

For technical information or an MSDS regarding this product contact Huestone.

Contact

t: +61 3 9314 9303

f: +61 3 9314 6296

e: ask@huestone.com

w: huestone.com



huestone
concrete couture