

Huestone Dense Stone Sealer is a solvent-based sealer, which is designed to penetrate dense stone, sealing the pores yet leaving the stone with a natural finish. Once cured it will protect the stone from water and salt damage as well as provide stain resistance and graffiti protection. Huestone Dense Stone Sealer has been designed to work in conjunction with Huestone Natural Finish. It is ideal for wet-area applications.

Benefits

- Solvent based sealer to penetrate dense stone.
- Protects from water and salt damage.
- Provides graffiti protection and stain resistance.
- Suits bluestone, vitrified, marble and granite.

Application

- ⇒ For best results ensure the surface to be sealed is cleaned thoroughly.
- ⇒ Ensure the surface is free from grease and dirt and that any prior coatings have been removed.
- ⇒ For heavily soiled floors it is recommended that a combination of Huestone Heavy Duty Degreaser (HDD) and Huestone Neutral Clean are used. Once the floor is free from contamination and dry, the sealing process can start.
- ⇒ Always test product on a small area first. And allow a 24-hour cure time to determine the ease of application and desired results.
- ⇒ Two coats of Huestone Dense Stone Sealer should be applied with a low-pressure pump (non electric) or a lambs wool applicator.

- ⇒ Allow 10 minutes for product to penetrate surface then wipe with a clean white dry cloth to remove excess product.
- ⇒ The initial coat coverage rate will vary between 5 and 15sqm/ltr depending on the porosity of the material.
- ⇒ Subsequent coats will attain a coverage rate of up to 20sqm. There will be a drying time of around 60 minutes between coats depending on weather and humidity.
- ⇒ The surface should be allowed 24 hours to fully cure and develop weather resistance.

Physical Properties

Colourless to slightly turbid
Mild petroleum
PH n/a
Specific gravity 0.83g/ml

Coverage

Smooth surfaces: 15-20sqm/ltr
Rough surfaces: 8-10sqm/ltr

Packaging

Available in 1, 5, 20ltr containers

For technical information or an MSDS regarding this product contact Huestone.

Contact

t: +61 3 9314 9303 f: +61 3 9314 6296
e: ask@huestone.com w: huestone.com



huestone **STONE**
concrete couture