

NATURAL FINISH STONE SEAL

huestone.com

Huestone Natural Finish Stone Sealer is a state-of-the-art solvent based sealer which is designed to penetrate the stone leaving it with a natural finish. Provides protection against graffiti and both water and oil based contaminants while permitting vapour and salt transmissions. Suitable for the use on concrete, limestone, sandstone, marble and all other porous earthen materials.

Benefits

- Solvent-based sealer designed to penetrate stone leaving a natural finish.
- Protects against graffiti, water and oil based contaminants while permitting vapour and salt transmissions.
- Suits concrete, limestone, sandstone, marble and all other porous stone materials.

Application

- ⇒ For best results ensure the surface to be sealed is cleaned thoroughly.
- ⇒ Ensure the surface is free from grease and dirt and that any prior coatings have been removed.
- ⇒ For heavily soiled floors it is recommended that a combination of Huestone Heavy Duty Degreaser (HDD) and Huestone Neutral Clean are used.
- ⇒ Once the floor is free from contamination and dry, the sealing process can start.
- ⇒ Always test product on a small area first. And allow a 24-hour cure time to determine the ease of application and desired results.

- ⇒ Two coats of Huestone Natural Finish Stone Sealer should be applied with a low-pressure pump (non electric) or a lambs wool applicator.
- ⇒ Allow 10 minutes for product to penetrate surface then wipe with a clean white dry cloth to remove excess product.
- ⇒ The initial coat coverage rate will vary between 5 and 15sqm/ltr depending on the porosity of the material.
- ⇒ Subsequent coats will attain a coverage rate of up to 20sqm. There will be a drying time of around 60 minutes between coats depending on weather and humidity.
- ⇒ The surface should be allowed 24 hours to fully cure and develop weather resistance.

Physical Properties

Colourless to yellowish haze
Mild solvent
PH n/a
Specific gravity 0.8

Coverage

Smooth surfaces: 15-20sqm/ltr
Rough surfaces: 8-10sqm/ltr

Packaging

Available in 1, 5, 20ltr containers

For technical information or an MSDS regarding this product contact Huestone.

Contact

t: +61 3 9314 9303

f: +61 3 9314 6296

e: ask@huestone.com

w: huestone.com



huestone
concrete couture